

POLARIS

TECHNICAL SHEET R58

R58 TRASPARENTE SOLIDO

Thixotropic transparent glue

A) DESCRIPTION AND FIELDS OF APPLICATION:

Pasty compound characterized by high thixotropy and transparency. Very suitable for vertical jobs and for repair of material already fixed. Once hardened, it takes on all the characteristics of the marble and can be worked with the ordinary tools and machineries employed for the marble itself. It offers excellent adhesion to all natural stones, like marble, granite, onyx and good adhesion to wood, concrete, ceramic. Provides an all special flow allowing to save 20% labour. Can be easily coloured by the addition of paste pigments for polyesters.

B) TECHNICAL DATA:

Composition	Unsaturated polyester resin.
Specific weight	1,15 ± 0,05
Available colours	Clear strow
Safety data	See safety data sheet

C) SURFACE PREPARATION :

* Make sure surface is free from dust and grease and perfectly dry.

D) CAUTIONS:

- * Mix well the glue with 1-3 % paste hardener.
- * Do not exceed with hardener ratio.
- * Do not utilize the product at temperature below 5°C.
- * Store in a cool and dry place.

POLARIS

TECHNICAL SHEET R58

R58 TRASPARENTE SOLIDO

Thixotropic transparent glue



1-3 % C10 paste hardener Pot life >7' at 20°C



Application by putty knife



<40' at 20°C



4-5' at 1 m.

F) TOOLS CLEANING:

* With nitro thinner.

G) FURTHER STEPS:

Ordinary sanding and polishing operations

Technical indications and advices are based on our own experiences. We assure the perfect quality of products. However, being the utilization out of our control, we assume no responsibility on the results obtained