

POLARIS

TECHNICAL SHEET R59

R59 POLICRISTAL SOLIDO

Polyester colourless solid glue

A) DESCRIPTION AND FIELDS OF APPLICATION:

Pasty compound for marbles, stones and granites, based on polyester resins. Its main feature is to be totally colourless and permanently light-resistant. Especially suitable for invisible repairing and artistic precision jobs; cementing and filling jobs of white marbles, without forming halos; treatment of travertin slabs and for filling up the hollow parts, without altering their aesthetic features. It can be easily coloured by the addition of paste pigment for polyesters and nacre.

B) TECHNICAL DATA:

Composition	Unsaturated polyester resin.
Specific weight	1,1 ± 0,05
Available colours	Clear colourless
Safety data	See safety data sheet

C) SURFACE PREPARATION :

* Make sure surface is free from dust and grease and perfectly dry.

D) CAUTIONS:

- * Mix well the glue with 1-3 % liquid hardener.
- * Do not exceed with hardener ratio.
- * Do not utilize the product at temperature below 5°C.
- * Store in a cool and dry place.

POLARIS

TECHNICAL SHEET R59

R59 POLICRISTAL SOLIDO

Polyester colourless solid glue



1-3 % C09 liquid hardener Pot life >9' at 20°C



Application by putty knife



<40' at 20°C



4-5' at 1 m.

F)TOOLS CLEANING:

* With nitro thinner.

G)FURTHER STEPS:

On thin layers await at least 10 hours before smoothing and polishing operations.

Technical indications and advices are based on our own experiences. We assure the perfect quality of products. However, being the utilization out of our control, we assume no responsibility on the results obtained